TEKNIKUM

Teknikum FOOD-TEK® SD Light



APPLICATIONS

Teknikum FOOD-TEK® SD Light is a plastic spiral reinforced suction and delivery hose for transferring milk, beer, wine and strong alcohols.

The hose is reelable and as such suitable for filling and discharging milk tankers – it's light, extremely flexible and reshapes after compression.

ADVANTAGES

- Safe and durable hose
- Extremely flexible
- Light weight and easy handling
- Reshapes after compression
- High mechanical strength
- Hose can be cut on-site

COMPLIANCY / STANDARD

The hose is compliant with these food contact material regulations:

- EU regulation: No. 1935/2004.
- FDA regulation: No. 21 CFR 177.2600.
- German regulation: BfR recommendation XXI category 2.

TECHNICAL PROPERTIES

Previous versions

FOOD-TEK® 1120 PS (same reference and structure)

Structure

- Tube:
 - o white NR
 - approved food contact material
 - o smooth
- Reinforcement:
 - o textile and plastic spiral
- Cover:
 - o blue NR
 - weather and abrasion resistant
- Safety factor: 4

Temperature range

-40°C...+80°C (temporarily +120°C)

WASHING

Before using in food industry the hoses must be washed with 5% soda solution. Ask alternative washing and disinfection recommendations from our sales.

SUITABLE COUPLINGS AND CLAMPS

We recommend Teknikum Dairy coupling and recommended clamps are swaged clamp or SL-clamp.

MANUFACTURER

Teknikum Oy (Business ID F107645274), Nokiankatu 1, 38210, Sastamala, Finland

More information

sales@teknikum.com www.teknikum.com



All rights reserved. © 2020 Teknikum Group Ltd.











ORDER REFERENCE

| Product code | Ø i.d. mm | Ø o.d. mm | Working press. MPa | Vacuum max. MPa | | Weight kg/m | Length m |
|--------------|--------------|--------------|--------------------------|--------------------|-----|----------------|-------------|
| FOOD051PS | 51 | 64 | 0,6 | 0,09 | 160 | 1,40 | 40 |
| FOOD053PS | 53 | 66 | 0,6 | 0,09 | 160 | 1,40 | 40 |
| FOOD063PS | 63 | 78 | 0,6 | 0,09 | 220 | 1,80 | 40 |
| FOOD065PS | 65 | 80 | 0,6 | 0,09 | 220 | 1,90 | 40 |

Other dimensions available on request.

