

# LACTO-TEK® 1420 SL

 [teknikum.com/en/food-quality-hoses/lacto-tek-1420-sl-2](https://teknikum.com/en/food-quality-hoses/lacto-tek-1420-sl-2)



## Suction and pressure hose

### Applications:

Suction- and pressure hose for food industry and other process industries with high hygienic demands.

### TEMPERATURE RANGE:

-30°C...+80°C (temporarily washing with steam +130°C)

### CONSTRUCTION:

**Tube:** white NBR, resistant to fats and cooking oils, FDA-approved food quality

**Reinforcement:** textile and steel spiral

**Cover:** blue NBR/PVC, wear resistant

**Safety factor:** 4

### NOTE:

Before using in food industry the hoses must be washed with 5% soda solution. Ask alternative washing and disinfection recommendations from our sales. We recommend dairy coupling. Recommended clamps are swaged clamp or SL-clamp.

## Technical information

Product code	Ø i.d. mm	Ø o.d. mm	Working press MPa	Vacuum max. MPa	Bending radius mm	Weight kg/m	Length m
1420SL025	25	37	1,0	0,09	60	0,90	40
1420SL040	40	53	1,0	0,09	110	1,50	40

<b>Product code</b>	<b>∅ i.d. mm</b>	<b>∅ o.d. mm</b>	<b>Working press MPa</b>	<b>Vacuum max. MPa</b>	<b>Bending radius mm</b>	<b>Weight kg/m</b>	<b>Length m</b>
1420SL050	50	66	1,0	0,09	140	2,20	40
1420SL051	51	62	1,0	0,09	140	1,80	40
1420SL065	65	79	1,0	0,09	180	2,60	40
1420SL075	75	91	1,0	0,09	220	3,30	40
1420SL076	76	92	1,0	0,09	220	3,30	40

## Sales - Industrial hoses

**The Nordic Countries** • [sales@technikum.com](mailto:sales@technikum.com)

**Central Europe** • [sales.de@technikum.com](mailto:sales.de@technikum.com)

**Russia** • [sales.ru@technikum.com](mailto:sales.ru@technikum.com)