

Teknikum FUEL-TEK® D LYPO



APPLICATIONS

Reliable delivery hose for gasoline, diesel oil and oil mixed water.

Suitable for lead-free and E10 gasoline.

ADVANTAGES

- Safe and durable hose
- Great for E10 gasoline
- Smooth cover
- Long length coils

TECHNICAL PROPERTIES

Structure

- Tube: black NBR
 - smooth
 - fuel and oil resistant
- Reinforcement: textile
- Cover: black NBR/PVC
 - smooth
 - oil and weather resistant
- Burst safety factor: 3 x working press.
- Electrical resistance $R \leq 10^6 \Omega$

Temperature range

-20°C...+80°C

SUITABLE COUPLINGS AND CLAMPS

Recommended clamp is band clamp.

MANUFACTURER

Teknikum Oy (Business ID FI07645274),
Nokiankatu 1, 38210, Sastamala, Finland

More information

sales@teknikum.com








www.teknikum.com

All rights reserved. © 2022 Teknikum Group Ltd.



ORDER REFERENCE

Selected sizes available directly from stock. Ask more from sales.

Product code 	Ø i.d. mm 	Ø o.d. mm 	Working press. MPa 	Bending radius mm 	Weight kg/m 	Length m 
HLYP010005	5	12	1,0	35	0,20	60
HLYP010008	8	15	1,0	45	0,20	60
HLYP010010	10	17	1,0	70	0,20	60
HLYP010013	13	21	1,0	90	0,30	60
HLYP010016	16	24	1,0	120	0,30	60
HLYP010020	19	27	1,0	130	0,40	60
HLYP010025	25	34	1,0	175	0,60	60

MARKINGS



Also hose Ø included in the markings.