

MARI 2440

 teknikum.com/en/chemical-and-petrochemical-hoses/mari-2440-2



Delivery hose

Applications:

Delivery hose for transport of gasoline, diesel oil and oil mixed water. Suitable also for lead-free gasoline. As fuel hose for boats the hose meets requirements of standards (SFS-EN-) ISO 7840:2004 A2 and (SFS-EN-) ISO 8469:2006.

TEMPERATURE RANGE: -30°C...+100°C

CONSTRUCTION:

Tube: black NBR

Reinforcement: \varnothing i.d. < 32 mm textile ; \varnothing i.d. \geq 32 mm textile and steel spiral

Cover: black CR

Safety factor: 3

NOTE:

Recommended clamp is [swaged clamp](#) or [Kerko clamp](#) when \varnothing i.d. < 32 mm.

Technical information

Product code	\varnothing i.d. mm	\varnothing o.d. mm	Working press. MPa	Vacuum max. MPa	Bending radius mm	Weight kg/m	Length m
MARI008	8	18	0,8	0,080	75	0,30	40
MARI010	10	20	0,8	0,080	80	0,30	40
MARI013	12,5	22,5	0,8	0,035	90	0,40	40

Product code	Ø i.d. mm	Ø o.d. mm	Working press. MPa	Vacuum max. MPa	Bending radius mm	Weight kg/m	Length m
MARI016	16	26	0,8	0,035	100	0,50	40
MARI020	20	31	0,8	0,035	120	0,60	40
MARI025	25	37	0,8	0,035	150	0,70	40
MARI032	31,5	44,5	0,8	0,090	130	1,10	40
MARI038	38	51	0,8	0,090	150	1,20	40
MARI040	40	53	0,8	0,090	150	1,30	40
MARI045	45	58	0,8	0,090	160	1,40	40
MARI050	50	63	0,8	0,090	170	1,50	40
MARI063	63	77	0,8	0,090	190	1,90	40

Sales - Industrial hoses

The Nordic Countries • sales@technikum.com

Central Europe • sales.de@technikum.com

Russia • sales.ru@technikum.com