

## Teknikum LKM™ Thermoplastic



### APPLICATIONS

Designed for transporting oil and oil mixed water. Suitable e.g. as a water hose in windscreen washing system.

Material is thermoplastic, which withstands multiple heating and cooling cycles.

### ADVANTAGES

- Suitable for oil contact
- Safe and durable hose
- Thermoplastic properties

### TECHNICAL PROPERTIES

#### Previous versions

LKM™ (same reference and structure)

#### Structure

- Tube:
  - black
  - non-reinforced
  - TPE 715
  - hardness 70 ShA

#### Temperature range

-30°C...+100°C

### MANUFACTURER

Teknikum Oy (Business ID FI07645274),  
Nokiankatu 1, 38210, Sastamala, Finland

#### More information

[sales@teknikum.com](mailto:sales@teknikum.com)

[www.teknikum.com](http://www.teknikum.com)

© All rights reserved by Teknikum Group  
2020



## ORDER REFERENCE

Product code	Ø i.d. mm	Ø o.d. mm	Weight kg/m	Length m
LKM0204	2	4	0,01	100
LKM02505	2,5	5	0,02	100
LKM035065	3,5	6,5	0,03	100
LKM03509	3,5	9	0,07	50
LKM045085	4,5	8,5	0,05	50
LKM0511	5	11	0,09	50
LKM055095	5,5	9,5	0,06	50
LKM0612	6	12	0,10	50
LKM075115	7,5	11,5	0,08	50

Other dimensions available on request.

## REFERENCE IMAGE

