

## Teknikum NORA™ RADIATOR 0,6 Mpa



### APPLICATIONS

High quality multipurpose water hose for many different applications and specially designed for cooling systems.

### ADVANTAGES

- Safe and durable hose
- High flexible
- Excellent weather and ozone resistance
- Multipurpose

### TECHNICAL PROPERTIES

#### Previous versions

NORA™

(same reference and structure)

#### Structure

- tube:
  - black EPDM
  - smooth
- Reinforcement: textile
- Cover:
  - black EPDM
  - weather and ozone resistant
- Safety factor: 3 (Burst pressure = 3,0 x Working pressure)

#### Temperature range

-40°C...+110°C

### SUITABLE COUPLINGS AND CLAMPS

Recommended clamp is Teknikum hose clamp.

### MANUFACTURER

Teknikum Oy (Business ID FI07645274),  
Nokiankatu 1, 38210, Sastamala, Finland

#### More information

[sales@teknikum.com](mailto:sales@teknikum.com)

[www.teknikum.com](http://www.teknikum.com)

All rights reserved. © 2020 Teknikum Group Ltd.



## ORDER REFERENCE

| Product code     | Ø i.d.<br>mm | Ø o.d.<br>mm | Working<br>press.<br>MPa | Bending<br>radius mm | Weight<br>kg/m | Length<br>m |
|------------------|--------------|--------------|--------------------------|----------------------|----------------|-------------|
| <b>NORA06013</b> | 13           | 21           | 0,6                      | 90                   | 0,20           | 40          |
| <b>NORA06016</b> | 16           | 24           | 0,6                      | 100                  | 0,30           | 40          |
| <b>NORA06020</b> | 19           | 28           | 0,6                      | 120                  | 0,30           | 40          |
| <b>NORA06022</b> | 22           | 30           | 0,6                      | 130                  | 0,40           | 40          |
| <b>NORA06025</b> | 25           | 33           | 0,6                      | 150                  | 0,50           | 40          |
| <b>NORA06029</b> | 29           | 38           | 0,6                      | 155                  | 0,60           | 40          |
| <b>NORA06032</b> | 32           | 42           | 0,6                      | 160                  | 0,70           | 40          |
| <b>NORA06040</b> | 40           | 50           | 0,6                      | 220                  | 0,80           | 40          |
| <b>NORA06050</b> | 50           | 61           | 0,6                      | 410                  | 1,10           | 40          |
| <b>NORA06057</b> | 57           | 68           | 0,6                      | 450                  | 1,30           | 40          |
| <b>NORA06060</b> | 60           | 71           | 0,6                      | 480                  | 1,30           | 40          |
| <b>NORA06075</b> | 76           | 86           | 0,6                      | 560                  | 1,40           | 40          |

Other dimensions available on request.

## MARKINGS

