

TEKNIKUM®

Splash guard NR/SBR

black 65, reinforced, on roll



APPLICATIONS

Teknikum® Splash guard is manufactured from a mixture of natural rubber (NR) and styrene-butadiene rubber (SBR). This rubber material is pliable and has excellent cold-endurance properties. It is also very wear-resistant, and nylon enforcements make it extremely durable.

The splash guard material is designed for vehicles but can be also used to protect work other machines from splashes. Additionally, it can be used for protecting any surfaces with its excellent wear-resistance and tensile properties.

The rubber compound is made by Teknikum and awarded by "Made in Finland" Key Flag symbol.

ADVANTAGES

- Extremely durable, wear-resistant surface
- Designed for vehicles
- Nylon reinforcement
- Endures cold temperatures
- Easy to clean

TECHNICAL PROPERTIES

Structure

- Material: Mixture of natural rubber and styrene-butadiene rubber
- Hardness: 65±5 ShA
- Density: 1,4
- Nylon reinforcement:
 - 5 mm: 1 reinforcement
 - 6 mm: 2 reinforcements

Temperature range

- 40°C... +70°C

ENVIRONMENTAL RESISTANCE

- Weather-resistant
- Endures minus temperatures well

SERVICES & CUSTOM SHAPES

Special shapes can be cut from the sheet by a water jet cutter. Ask for a project offer.

STORAGE

When stored and used under the recommended conditions, the sheet's expected life is in minimum 3 years.

Recommended storage according to ISO 2230:2002 Rubber products — *Guidelines for storage*.

RECYCLING

For decommissioned sheets, the correct disposal method is recovery as energy waste, in an appropriate incineration process.

MANUFACTURER

Teknikum Ltd (Business ID FI07645274),
Sementtitehtaankuja 12, FI-04260 Kerava,
FINLAND

More information

sales@teknikum.com

www.teknikum.com

All rights reserved. © 2023 Teknikum Group Ltd.



ORDER REFERENCE

Product code	Thickness mm	Roll size W x L m*	Rubber quality	Weight/roll (nominal w)	Marking color	Color	MOQ
SLRLEV0506	5 mm	0,6 x 10	NR/SBR	42 kg	-	Black	4 rolls
SLRLEV0512	5 mm	1,2 x 10	NR/SBR	84 kg	-	Black	2 rolls
SLRLEV0606	6 mm	0,6 x 10	NR/SBR	50 kg	-	Black	2 rolls
SLRLEV0612	6 mm	1,2 x 10	NR/SBR	101 kg	-	Black	2 rolls

* 33m maximum roll length, unfinished

AVAILABILITY (table text color)

Blue = on stock

Grey = project orders on demand, check availability from sales.

REFERENCE IMAGES

