

Teknikum PAVE™ Hot Yellow Air/Water 3,0 MPa



APPLICATIONS

High-quality compressed air and hot water hose for demanding use.

This multipurpose hose is suitable for many different applications requiring high-pressure resistance, reliability, durability and long lifecycle.

EPDM hose is also suitable for diluted chemicals.

ADVANTAGES

- Safe and durable hose
- Great for hot water
- High burst pressure
- Excellent visibility due to the yellow cover
- Excellent weather- and ozone-resistance
- Multipurpose

TECHNICAL PROPERTIES

Structure

- Tube: black EPDM
 - smooth
 - heat resistant
- Reinforcement: textile
- Cover: yellow EPDM
 - smooth
 - weather and ozone resistant
 - non-staining
- Burst safety factor 3,2 x working press.

Temperature range

-40°C...+120°C

SUITABLE COUPLINGS AND CLAMPS

We recommend for band clamp or high-pressure couplings according to EN 14420 and clamps according to EN 14420-3. Please ensure the clamp suitability according to the hose dimension.

MANUFACTURER

Teknikum Oy (Business ID FI07645274),
Nokiankatu 1, 38210, Sastamala, Finland

More information

sales@teknikum.com








www.teknikum.com

All rights reserved. © 2022 Teknikum Group Ltd.



ORDER REFERENCE

Selected sizes available directly from stock. Ask more from sales.

Product code 	Ø i.d. mm 	Ø o.d. mm 	Working press. MPa 	Bending radius mm 	Weight kg/m 	Length m 
---	---	---	---	---	--	---

HPARAK30008	8	17	3,0	50	0,20	40
HPARAK30010	10	20	3,0	60	0,30	40
HPARAK30013	13	23	3,0	80	0,40	40
HPARAK30016	16	27	3,0	100	0,40	40
HPARAK30019	19	30	3,0	110	0,50	40
HPARAK30025	25	37	3,0	150	0,70	40
HPARAK30032	32	44	3,0	320	0,90	40
HPARAK30038	38	51	3,0	380	1,10	40
HPARAK30042	42	56	3,0	420	1,40	40
HPARAK30050	50	66	3,0	500	1,90	40

Other dimensions available on request.

MARKINGS

