

Teknikum BLAST-TEK® D



APPLICATIONS

Reliable high-quality sand and grit blasting hose with excellent inner tube quality. The hose is multipurpose and suitable also for concrete pumping and transferring highly abrasive materials such as quartz and granulates, etc.

This wear resistant hose is designed according to EN ISO 3861:2008 (Rubber hoses for sand and grit blasting) to fit commonly used sand blasting hose couplings.

Average wear of the tube 45 mm³ (according to DIN ISO 4649:2021).

ADVANTAGES

- Safe and durable hose
- Excellent resistance to abrasion
- Long service life
- Antistatic
- Quick and easy installation
- Hoses can be cut on-site

TECHNICAL PROPERTIES

Structure

- Tube: black NR
 - smooth
 - abrasion resistant
 - antistatic
- Reinforcement: textile
- Cover: black SBR
 - smooth
 - wear and weather resistant
 - antistatic
- Burst safety factor 4 x working press.

Temperature range

- 40°C... +80°C

SUITABLE COUPLINGS AND CLAMPS

Recommended coupling type is commonly used sand blasting couplings (e.g. Clemco or Lüdecke, please inquire from our sales) or band clamp.

MANUFACTURER

Teknikum Oy (Business ID FI07645274),
Nokiankatu 1, 38210, Sastamala, Finland








More information

sales@teknikum.com
www.teknikum.com



ORDER REFERENCE

Selected sizes available directly from stock. Ask more from sales.

| Product code  | Ø i.d. mm  | Ø o.d. mm  | Working press. bar  | Bending radius mm  | Weight kg/m  | Length m  |
|---|--|--|---|---|--|---|
| HBLAST013 | 13 | 27 | 12 | 40 | 0,6 | 40 |
| HBLAST019 | 19 | 33 | 12 | 60 | 0,7 | 40 |
| HBLAST025 | 25 | 39 | 12 | 100 | 1,0 | 40 |
| HBLAST032 | 32 | 48 | 12 | 130 | 1,3 | 40 |
| HBLAST038 | 38 | 56 | 12 | 160 | 1,5 | 40 |
| HBLAST050 | 50 | 72 | 12 | 220 | 2,0 | 40 |

Other dimensions and lengths on request.

MARKINGS

