

Teknikum MULTI-TEK™ SD UPE CLEAN



APPLICATIONS

Multipurpose suction and delivery hose corresponding to high quality standards in chemical industry. The hose endures approximately 98 % of the most common industrial chemicals.

The hose is designed for applications in the chemical, pharmaceutical and foodstuff industry.

The life cycle of the hose depends on the concentration and the temperature of transferred chemicals. Suitability of chemicals needs to be checked case specifically.

ADVANTAGES

- Multipurpose and suitable for almost all chemicals
- White FDA-approved UHMWPE lining with black electrical conductive spots
- Excellent weather and ageing resistance
- High mechanical strength
- High burst pressure $\geq 6,4$ MPa
- Suitable with many types of couplings

STANDARD/ COMPLIANCE

Meets the requirements of chemical hose standard EN 12115:2021.

FDA-approved material: CFR 21 § 177.1520.

EU regulation: No. 1935/2004, 10/2011.

ATEX compliance: EC 2014/34/EU, equipment group II / category 2.

TECHNICAL PROPERTIES

Structure

- Tube: white UHMWPE-film (Ultra High Molecular Weight Polyethylene)
 - smooth
 - chemical resistant
 - with black spots
 - FDA-approved material
- Reinforcement: textile and steel spiral
- Cover: blue EPDM
 - smooth
 - chemical resistant
 - wear and weather resistant
 - non-flammable
- Burst safety factor 4 x working press.

Temperature range

- 40°C... +100°C.

Electrical properties

- Meets the requirements of EN 12115:2021
- Hose type: Ω/T
- Conductive tube $R \leq 10^6 \Omega / \text{length}$
- Conductive through the hose wall $R \leq 10^9 \Omega$
- ATEX compliance (EC 2014/34/EU), equipment group II / category 2.

MAINTENANCE & NOTES

Washing

Before using in food industry, the hoses must be cleaned with steam. Please see Manufacturer declaration for more details.

SUITABLE COUPLINGS AND CLAMPS

We recommend hose couplings according to EN 14420-7 and clamps according to EN 14420-3.

MANUFACTURER

Teknikum Oy (Business ID FI07645274),
Nokiankatu 1, 38210, Sastamala, Finland









More information

sales@teknikum.com

www.teknikum.com



ORDER REFERENCE

Product code 	Ø i.d. mm 	Ø o.d. mm 	Working press. bar 	Vacuum max. bar 	Bending radius mm 	Weight kg/m 	Length m 
H2820WC019B	19	31	16	0,9	76	0,7	40
H2820WC025B	25	37	16	0,9	100	0,8	40
H2820WC032B	32	44	16	0,9	128	1,0	40
H2820WC038B	38	51	16	0,9	152	1,2	40
H2820WC040B	40	53	16	0,9	160	1,3	40
H2820WC050B	50	66	16	0,9	200	1,9	40
H2820WC063B	63	79	16	0,9	252	2,1	40
H2820WC075B	75	91	16	0,9	300	2,6	40
H2820WC076B	76	92	16	0,9	304	2,6	40
H2820WC100B	100	116	16	0,9	400	4,0	40
H2820WC102B	102	118	16	0,9	408	4,0	40

Other dimensions available on request.

MARKINGS



Also embossed standard markings:

TEKNIKUM - EN 12115:2021 - UPE - FDA - SD - (id) - 16bar - -40°C/+100°C - Ω/T - quarter/year