

Teknikum GRANIT®



APPLICATIONS

Robust and flexible material handling hose with corrugated cover for handling very abrasive substances. The hose is designed for hydraulic suction and delivery transportation of abrasive materials and suitable for heavy circumstances where the hose must resist wear, movements and damp vibrations.

Customized Teknikum GRANIT® hoses can be manufactured according to ISO 28017:2011 (rubber hoses and hose assemblies, wire or textile reinforced, for dredging applications) type 2.

Teknikum GRANIT® hoses can also be made of EPDM or NBR rubber materials.

Hose has antistatic properties, providing electrical conductivity and increased safety against ESD.

ADVANTAGES

- Safe and durable material handling hose
- Excellent resistance to abrasion and weather
- Eliminates vibrations and noise
- High burst pressure $\geq 3,2$ MPa
- Very flexible and low bending radius due to corrugated cover structure
- EPDM and NBR options
- Quick and easy installation
- Hoses can be cut on-site
- Complete with GRANIT® Select couplings

TECHNICAL PROPERTIES

Structure

- Tube: black NR 43 ShA
 - smooth
 - wear resistant
 - antistatic
- Reinforcement: textile and steel spiral
- Cover: black SBR
 - 20 % renewable raw materials
 - corrugated surface
 - wear and weather resistant
 - antistatic
- Burst safety factor 3,2 x working pressure

Temperature range

- 40°C... +80°C.

Electrical properties

- Conductive tube and cover $R \leq 10^6 \Omega$ / length
- Conductive through the hose wall $R \leq 10^9 \Omega$

SUITABLE COUPLINGS AND FLANGES

We recommend Teknikum GRANIT® Select couplings and Select gaskets. Available also with Teknikum PLUS™ flange system.

MANUFACTURER

Teknikum Oy (Business ID FI07645274),
Nokiankatu 1, 38210, Sastamala, Finland

More information










sales@teknikum.com

www.teknikum.com



ORDER REFERENCE

Selected sizes available directly from stock. Ask more from sales.

Product code 	Ø i.d. mm 	Ø o.d. mm 	Working press. bar 	Vacuum max. bar 	Bending radius mm 	Weight kg/m 	Length m 
Teknikum GRANIT® 							
H4180025	25	53	10	0,9	120	2,2	40
H4180032	32	60	10	0,9	150	2,6	40
H4180040	40	73	10	0,9	150	3,8	40
H4180050	50	83	10	0,8	200	3,8	40
H4180065	65	98	10	0,8	200	4,7	40
H4180080	80	113	10	0,8	200	5,7	40
H4180102	102	133	10	0,8	250	7,9	20
H4180127	127	164	10	0,8	350	10,4	20
H4180152	152	189	10	0,8	500	12,0	20
H4180203	203	246	10	0,8	1000	18,0	10
H4180253	253	293	10	0,8	1700	20,6	10
H4180300	300	352	10	0,8	1900	31,0	10
H4180305	305	352	10	0,8	1900	31,0	10
H4180350	350	407	10	0,8	2200	41,0	10

Other dimensions available on request.

MARKINGS



REFERENCE IMAGES

With recommended coupling **Teknikum GRANIT® Select**



Available also with **Teknikum PLUS™** flange system

