

Teknikum FUEL-TEK® D MARI



APPLICATIONS

Delivery oil hose for transportation of almost all oil-based materials and hydrocarbons with maximum aromatic content of 50%. The hose is suitable for gasoline, diesel oil and oil mixed water.

The hose can be used also with biodiesels which have less than 20% FAME (Fatty acid methyl ester) and with bioethanol containing biofuels.

ADVANTAGES

- Suitable for almost all petroleum-based products
- Multipurpose
- Excellent weather and ageing resistance
- High mechanical strength

STANDARD/ COMPLIANCE

As fuel hose for boats the hose meets requirements of standards SFS-EN ISO 7840:2004 A2 and SFS-EN ISO 8469:2006

TECHNICAL PROPERTIES

Structure

- Tube: black NBR
 - smooth
 - oil and fuel resistant
- Reinforcement:
 - $\varnothing$ i.d. < 32 mm textile
 - $\varnothing$ i.d. $\geq$ 32 mm textile and steel spiral
- Cover: black CR
 - smooth
 - wear and weather resistant
- Burst safety factor: 3 x working press.

Temperature range

- 30°C... +100°C.

SUITABLE COUPLINGS AND CLAMPS

We recommend band clamp for hose tightening. Swaged clamp is also suitable when $\varnothing$ i.d. < 32 mm.

MANUFACTURER

Teknikum Oy (Business ID FI07645274),
Nokiankatu 1, 38210, Sastamala, Finland

More information

sales@teknikum.com

www.teknikum.com



ORDER REFERENCE

Product code 	Ø i.d. mm 	Ø o.d. mm 	Working press. bar 	Vacuum max. bar 	Bending radius mm 	Weight kg/m 	Length m 
HMARI008	8	18	8	0,8	75	0,3	40
HMARI010	10	20	8	0,8	80	0,3	40
HMARI013	12,5	22,5	8	0,3	90	0,4	40
HMARI016	16	26	8	0,3	100	0,5	40
HMARI020	20	31	8	0,3	120	0,6	40
HMARI025	25	37	8	0,3	150	0,7	40
HMARI032	31,5	44,5	8	0,9	130	1,1	40
HMARI038	38	51	8	0,9	150	1,2	40
HMARI040	40	53	8	0,9	150	1,3	40
HMARI045	45	58	8	0,9	160	1,4	40
HMARI050	50	63	8	0,9	170	1,5	40
HMARI063	63	77	8	0,9	190	1,9	40

Other dimensions available on request.

MARKINGS



Reinforcement: Ø i.d. < 32 mm textile, Ø i.d. ≥ 32 mm textile and steel spiral