

Teknikum BLAST-TEK® D



APPLICATIONS

Reliable high-quality sand and grit blasting hose with excellent inner tube quality. The hose is multipurpose and suitable also for concrete pumping and transferring highly abrasive materials such as quartz and granulates, etc.

This wear resistant hose is designed according to EN ISO 3861:2008 (Rubber hoses for sand and grit blasting) to fit commonly used sand blasting hose couplings.

ADVANTAGES

- Safe and durable hose
- Excellent resistance to abrasion
- Long service life
- Antistatic
- Quick and easy installation
- Hoses can be cut on-site

TECHNICAL PROPERTIES

Structure

- Tube: black NR
 - smooth
 - abrasion resistant
 - antistatic
- Reinforcement: textile
- Cover: black SBR
 - smooth
 - wear and weather resistant
 - antistatic
- Burst safety factor 4 x working press.

Temperature range

- 40°C... +80°C

SUITABLE COUPLINGS AND CLAMPS

Recommended coupling type is commonly used sand blasting couplings (e.g. Clemco or Lüdecke, please inquire from our sales) or band clamp.

MANUFACTURER

Teknikum Oy (Business ID FI07645274),
Nokiankatu 1, 38210, Sastamala, Finland








More information

sales@teknikum.com
www.teknikum.com



ORDER REFERENCE

Selected sizes available directly from stock. Ask more from sales.

Product code 	Ø i.d. mm 	Ø o.d. mm 	Working press. bar 	Bending radius mm 	Weight kg/m 	Length m 
HBLAST013	13	27	12	40	0,6	40
HBLAST019	19	33	12	60	0,7	40
HBLAST025	25	39	12	100	1,0	40
HBLAST032	32	48	12	130	1,3	40
HBLAST038	38	56	12	160	1,5	40
HBLAST050	50	72	12	220	2,0	40

Other dimensions and lengths on request.

MARKINGS

